

Document made available under the Patent Cooperation Treaty (PCT)

International application number: PCT/US05/011346

International filing date: 01 April 2005 (01.04.2005)

Document type: Certified copy of priority document

Document details: Country/Office: US
Number: 60/558,140
Filing date: 01 April 2004 (01.04.2004)

Date of receipt at the International Bureau: 02 May 2005 (02.05.2005)

Remark: Priority document submitted or transmitted to the International Bureau in compliance with Rule 17.1(a) or (b)



World Intellectual Property Organization (WIPO) - Geneva, Switzerland
Organisation Mondiale de la Propriété Intellectuelle (OMPI) - Genève, Suisse

1313779

THE UNITED STATES OF AMERICA

TO ALL TO WHOM THESE PRESENTS SHALL COME:

UNITED STATES DEPARTMENT OF COMMERCE

United States Patent and Trademark Office

April 26, 2005

THIS IS TO CERTIFY THAT ANNEXED HERETO IS A TRUE COPY FROM THE RECORDS OF THE UNITED STATES PATENT AND TRADEMARK OFFICE OF THOSE PAPERS OF THE BELOW IDENTIFIED PATENT APPLICATION THAT MET THE REQUIREMENTS TO BE GRANTED A FILING DATE.

APPLICATION NUMBER: 60/558,140

FILING DATE: *April 01, 2004*

RELATED PCT APPLICATION NUMBER: *PCT/US05/11346*



Certified by

Under Secretary of Commerce
for Intellectual Property
and Director of the United States
Patent and Trademark Office



Atty. Dkt. No. 032968-0105

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE



Applicant: Lawrence Craig KENNEDY et al.

Title: CLUTCH ASSEMBLY

Appl. No.: Unassigned

Filing Date: April 1, 2004

Examiner: Unknown

Art Unit: Unknown

PROVISIONAL PATENT APPLICATION
TRANSMITTAL

Mail Stop PROVISIONAL PATENT APPLICATION
Commissioner for Patents
PO Box 1450
Alexandria, Virginia 22313-1450

Sir:

Transmitted herewith for filing under 37 C.F.R. § 1.53(c) is the provisional patent application of:

Lawrence Craig KENNEDY
4865 Ledgewood Drive
Commerce Township, MI 48382

James F. GALLAGHER
1151 North Alstott Drive
Howell, MI 48843

Philip STEPHENSON
2740 Bent Tree Drive
Dexter, MI 48130

Gregory MACK
1476 Adams Street
P.O. Box 49
Dansville, MI 48819

[] Applicant claims small entity status under 37 CFR 1.27(c)(1).

Enclosed are:

- ☒ Specification and Claim(s) (44 pages).
- ☒ Informal drawings (21 sheets, Figures 1-18).
- ☒ Application Data Sheet (37 CFR 1.76).

The filing fee is calculated below:


| | Rate | Fee Totals |
|---|----------|-----------------|
| Basic Fee | \$160.00 | \$160.00 |
| <input type="checkbox"/> Small Entity Fees Apply (subtract ½ of above): | = | \$0.00 |
| TOTAL FILING FEE: | = | \$160.00 |

- ☒ A check in the amount of \$160.00 to cover the filing fee is enclosed.
- ☐ The required filing fees are not enclosed but will be submitted in response to the Notice to File Missing Parts of Application.
- ☐ Further, Applicant, by and through his attorney of record, hereby expressly abandons the application as of the filing date of this letter. This is an abandonment of the application only, and is not to be construed as an abandonment of the invention disclosed in the application. It is respectfully requested that the Office acknowledge abandonment of the application as of the filing date of this letter in a communication mailed to the undersigned.
- ☒ The Commissioner is hereby authorized to charge any additional fees which may be required regarding this application under 37 C.F.R. §§ 1.16-1.17, or credit any overpayment, to Deposit Account No. 19-0741. Should no proper payment be enclosed herewith, as by a check being in the wrong amount, unsigned, post-dated, otherwise improper or informal or even entirely missing, the Commissioner is authorized to charge the unpaid amount to Deposit Account No. 19-0741.

Please direct all correspondence to the undersigned attorney or agent at the address indicated below.

Respectfully submitted,

By



Date: April 1, 2004

FOLEY & LARDNER LLP
Customer Number: 22428
Telephone: (202) 672-5414
Facsimile: (202) 672-5399

Richard L. Schwaab
Attorney for Applicant
Registration No. 25,479

CLUTCH ASSEMBLY

BACKGROUND

[0001] The present invention relates to a clutch assembly. More particularly, the present invention relates to a more robust and readily manufacturable viscous fluid clutch (e.g., a magnetorheological fluid (MRF) clutch) for a fan drive assembly for use in a vehicle.

[0002] A viscous fluid clutch typically includes a viscous material, such as a magnetorheological fluid, operating in a gap between a driven rotor and a stator where the stator couples with the rotor to drive an output speed of the clutch and an attached fan blade assembly. Magnetorheological fluids typically include finely divided iron particles suspended in a non-polar medium. Magnetorheological fluids are preferably formulated to resist particle separation even under high separation force applications and typically function as Bingham fluids. In an ambient gravitational field and in the absence of a magnetic field, a Bingham fluid displays a shear stress that increases generally linearly as the shear rate on the fluid is increased. When a Bingham fluid is subjected to a magnetic field, the shear stress versus shear rate relationship is increased so that substantially more shear stress is required to commence shear of the fluid. Such a characteristic is useful in controlling transfer of torque between the rotor and the stator in an MRF clutch.

[0003] The known design of a viscous fluid clutch further includes a coil for creating an electromagnetic field in gaps between the rotor and the stator. When the magnetorheological fluid is subjected to the electromagnetic field, the yield stress of the magnetorheological fluid varies and the speed at which the stator is coupled to the rotor varies. In this manner, the output speed of the clutch is infinitely variable with respect to the input speed.

[0004] In an engine driven fan system employing an MRF clutch, the speed of the fan is continuously variable by varying a magnetic flux in the magnetorheological fluid. Such variable speed fan drive assemblies provide

improved fuel economy, noise reduction, improved power train cooling, and cost reduction. However, conventional MRF clutches can involve excessive manufacturing cost and labor.

[0005] For example, in practice, all fan clutches, including conventional MRF clutches, have typically required the use of four or more fasteners to attach a fan blade hub to a fan cover body. The greater the number of fasteners, the greater the weight and cost of the final product and the more time required for manufacturing assembly.

[0006] Conventional MRF clutches also include a rotor having a slot, or a series of discontinuous slots (or other feature), to prevent the magnetic field from prematurely shunting across the rotor. The creation of the slots (or other shunt prevention feature) requires the rotor to undergo a complex additional machining process, which increases manufacturing cost and time.

[0007] Another disadvantage of conventional MRF clutches is that such clutches have proven to not be sufficiently robust for application in vehicles. For example, such clutches may include leak paths that enable the magnetorheological fluid to escape from the clutch as the MRF seeps into an internal porous portion of the cast aluminum fan cover body. Although the shell (or skin) of the casting generally prevents the fluid from leaking beyond the internal porous portion of the casting, bolt holes for attachment of the fan blade hub include machined threads. The machining process breaches the shell of the casting (which is created during the casting process) to expose the internal porous portion thereby providing a leak path for the escape of the magnetorheological fluid. Similarly, magnetorheological fluid can leak out of the clutch along a path formed by areas of contact between the cast fan cover body and a metal fan cover insert.

[0008] Additionally, in conventional MRF clutches, problems may arise during clutch operation. For example, in such clutches the clutch cover is typically positioned around a ferrous material cover insert. During operation of the clutch, the clutch cover and the clutch cover insert may tend to separate. Similarly, the rotor hub of such clutches may experience

dimensional changes due to increased temperature during clutch operation. The dimensional changes can cause the rotor hub (and/or the rotor, which is attached to the rotor hub) to contact the clutch housing during operation.

[0009] MRF clutches typically generate a significant amount of heat due to viscous heating and are susceptible to damage from overheating. One disadvantage of conventional MRF fan clutches is that such clutches typically rely solely on incoming air flow (i.e., ram air) to cool the clutch. The ram air is generated by motion of the vehicle. When vehicle speed is low (e.g., at engine idle, during severe grade towing, travel with a significant tailwind), the velocity and volume of ram air flowing over the clutch may be insufficient to effectively cool the clutch. The velocity and volume of ram air reaching the fan clutch is also affected by restrictions to the free flow of incoming air, such as the vehicle front end, the radiator, the grille assembly, and the hood latch mechanism.

[0010] Additionally, conventional MRF clutches do not effectively direct the ram air to the cooling fins of the clutch. Due to clutch geometry, air flowing toward the clutch may stagnate or bypass the cooling fins so that heat is not effectively dissipated. For example, such clutches typically have an electrical cap connected to the fan clutch at a central area on the front of the clutch. The electrical cap creates a stagnation point so that heat cannot be effectively dissipated from the central area of the clutch. As a result, performance and overall durability of the clutch are reduced.

[0011] In a vehicle system, an MRF fan clutch is typically driven by the same pulley that drives the water pump. For example, a drive belt from the crankshaft pulley turns a water pump pulley, which drives both the water pump and the fan clutch. One disadvantage of such an arrangement is that the water pump and the fan clutch generally require different input speeds. Thus, the fan clutch must be stepped-up using an appropriate gear (pulley) device so that the input shaft of the fan clutch rotates at a proportionately higher speed than engine speed. Selection of the pulley ratio of the gear device requires a compromise between fan speed and water pump speed. If

the ratio is too high, the fan speed may be excessive even though the water pump speed satisfies the demand for coolant flow. Excessive fan speed can cause premature failure of the fan clutch. Conversely, if the ratio is too low, the fan speed will provide insufficient airflow to the coolant flowing through the radiator resulting in diminished air conditioning performance at idle.

BRIEF DESCRIPTION OF THE DRAWINGS

[0012] The accompanying drawings, which are herein incorporated and constitute a part of this specification, illustrate embodiments of the invention and together with the description serve to explain principles of the invention.

[0013] Figure 1 is a cross sectional side elevation view of an embodiment of a clutch assembly according to the present invention.

[0014] Figure 2 is a cross sectional side view of a rotor of Fig. 1.

[0015] Figure 2A is a perspective view of the rotor and a rotor hub of Fig. 1.

[0016] Figure 2B is a cross sectional side view of the rotor hub of Fig. 1.

[0017] Figure 3 is a rear elevation view of a clutch housing assembly of Fig. 1.

[0018] Figure 4 is a side elevation view of the clutch housing assembly of Fig. 3.

[0019] Figure 5 is a perspective view of the clutch housing assembly of Fig. 3.

[0020] Figure 5A is a perspective view of the clutch housing assembly of Fig. 5 showing a fan blade assembly attached thereto.

[0021] Figure 5B is a rear perspective view of the fan blade assembly of Fig. 5A.

[0022] Figure 6 is a view of detail A in Fig. 1 showing engagement of a clutch housing assembly cover and cover insert.

[0023] Figure 6A is a side elevation view of the insert of Fig. 6 without the cover.

[0024] Figure 6B is a view of the cover and insert of Fig. 6 showing the insert separated from the cover.

- [0025] Figure 6C is a side elevation view of the housing insert of Fig. 6A prior to a machining operation.
- [0026] Figure 7 is a perspective view of a coil assembly of Fig. 1.
- [0027] Figure 7A is a cross sectional view of a brush box of Fig. 1.
- [0028] Figure 8 is a cross sectional side elevation view of the coil assembly of Fig. 7.
- [0029] Figure 9 is a perspective view of an embodiment of a cooling device installed on a clutch assembly according to the present invention.
- [0030] Figure 10 is a cross sectional view of the cooling device and clutch assembly of Fig. 9 showing air flow through the cooling device.
- [0031] Figure 11 is a perspective view of the cooling device of Fig. 9.
- [0032] Figure 12 is a cross sectional side view of the cooling device of Fig. 9.
- [0033] Figure 13 is a bottom perspective view of the cooling device of Fig. 9.
- [0034] Figure 14 is a perspective view of an attachment member of Fig. 9.
- [0035] Figure 15 is a front perspective view of cooling fins on a clutch assembly cover according to an embodiment of the present invention.
- [0036] Figure 16 is a section view taken along line B-B of Fig. 16A showing a tri-lobular shape of a fastener thread.
- [0037] Figure 16A is perspective side view partly in section of a self-tapping fastener installed in a cover of a clutch housing assembly according to an embodiment of the present invention.
- [0038] Figure 16B is a view of detail B of Fig. 16A.
- [0039] Figure 17 is a cross sectional side elevation view of an embodiment of an MRF drive device according to the present invention.
- [0040] Figure 18 is view of detail A of Fig. 17 including a permanent magnet.

DETAILED DESCRIPTION OF PREFERRED EMBODIMENTS

[0041] As background, MRF clutches are described in U.S. Patents No. 5,823,309; No. 5,845,752; No. 5,848,678; No. 5,896,964; No. 5,896,965; No. 5,960,918; No. 6,032,772; No. 6,102,177; No. 6,173,823; No. 6,318,531; and No. 6,585,092. The entire disclosure of each of these patents are herein incorporated by reference.

[0042] Figure 1 shows an embodiment of a magnetorheological fluid (MRF) clutch 1 for a fan drive assembly according to an embodiment of the present invention. In this embodiment, the MRF clutch 1 generally includes an input shaft 10, a rotor hub 20, a rotor 30, a clutch housing assembly 40, a coil assembly 80, and a tether assembly 120.

[0043] The input shaft 10 (shown in Fig. 1) is configured to supply rotational input force to the MRF clutch 1. The input shaft 10 rotates about an axis A-A and can be driven by an engine of a vehicle, for example, using a pulley driven by a crankshaft or other input device. Accordingly, a speed of the input shaft 10 is engine speed or is stepped-up using an appropriate gear device to make the input shaft 10 rotate at a proportionately higher speed than the engine speed. The input shaft 10 can be made, for example, of metal, such as steel, or any other known or appropriate material.

[0044] The MRF clutch 1 includes a rotor hub 20 configured to receive rotational input force from the input shaft 10. As shown in Figs. 2A and 2B, the rotor hub 20 preferably has an annular shape with an outer periphery 22 and an inner periphery 24. As shown in Fig. 2A, the annular shape of the rotor hub 20 is substantially round (or circular) for rotation about a center axis, such as the axis of rotation A-A of the input shaft 10. The inner periphery 24 of the rotor hub 20 includes a annular neck 26 affixed to the input shaft 10. The rotor hub 20 extends radially outward from the input shaft 10, and the outer periphery 22 of the rotor hub 20 is connected to an end of the rotor 30. The rotor hub 20 can be made from any known method but is preferably stamped from metal, such as aluminum.

[0045] The rotor hub 20 can optionally include a plurality of holes (not shown) to reduce the weight of the rotor hub 20 and to balance pressure on each side of the rotor hub 20. The rotor hub 20 can also include breathing passages 21 in the form of several holes radially and angularly spaced about the rotor hub 20 to equalize pressure on both sides of the rotor hub 20. The breathing passages can be disposed near a center of the rotor hub 20 (as shown in Fig. 2A) so that the breathing passages 21 are outside a shear zone of the magnetorheological fluid. The breathing passages 21 can be, for example, equally spaced with each breathing passage 21 having a diameter of approximately 5 mm to 7 mm.

[0046] The rotor hub 20 can also include a formed (curved) portion 28 (shown in Fig. 2B) extending annularly around the rotor hub 20. The formed portion 28 is disposed between the outer periphery 22 and the inner periphery 24 of the rotor hub 20. The formed portion 28 is configured to compensate for dimensional changes of the rotor hub 20 due to temperature variation during operation of the MRF clutch 1 by preventing radial movement of the outer periphery 22 of the rotor hub 20. For example, the formed portion 28 can include a concave surface 28a and a convex surface 28b. As shown in Fig. 1, the concave surface 28a is disposed on the side of the rotor hub 20 facing toward a direction of extension of the rotor 30 (e.g., toward a fan cover body 52). The convex surface 28b is disposed on the opposite side of the rotor hub 20, that is, on the side of the rotor hub 20 facing a direction that is opposite the direction of extension of the rotor 30 (i.e., facing toward a housing 42). Additionally, the concave surface 28a and the convex surface 28b are offset from the outer periphery 22 in a direction along the axis of rotation A-A of the input shaft 10 toward the housing 42. A radius of curvature of the concave surface 28a can be, for example, approximately 1.55 mm. Provision of the formed portion 28 provides a space (i.e., the space adjacent the concave surface 28a) into which the material of the rotor hub 20 can expand as the material grows during heating of the rotor hub 20. If the expansion space was not present (as with a conventional rotor hub), the outer periphery 22 of the

rotor hub 20 would bend (or pitch) toward the housing 42 and contact (or hit) the housing 42 thereby impairing operation of the clutch.

[0047] The rotor 30 is received within a slot 12 and is configured to rotate within the slot 12. As shown in Fig. 1, the slot 12 is defined by a wheel portion 54 and a ring portion 56 of a housing insert 150. The rotor 30 includes a ring having a first side 32 affixed to the outer periphery 22 of the rotor hub 20. For example, the first side 32 of the rotor 30 can be crimped onto the outer periphery 22 of the rotor hub 20 (shown in Fig. 1). The rotor 30 extends outwardly with respect to a face of the rotor hub 20 so that the first side 32 of the rotor 30 is closer to the rotor hub 20 than a second side 34 of the rotor 30, as shown in Fig. 1. The rotor 30 extends in a direction toward the fan cover body 52. The rotor 30 can be made of a magnetically permeable ferrous material, such as a low carbon steel alloy, preferably ASTM 1006 or ASTM 1008.

[0048] The rotor 30 can include a grooved portion 36 disposed between the first side 32 and the second side 34 of the rotor 30 to prevent a magnetic field from shunting along the rotor 30. The grooved portion 36 can be formed so that other portions (i.e., non-grooved portions) of the rotor 30 have a thickness that is sufficiently greater than a thickness of the grooved portion 36 to prevent a substantial path for magnetic flux across the rotor 30. For example, the thickness of the grooved portion 36 can be approximately 0.25 to 0.33 mm, and the thickness of first and second ends 32, 34 can be approximately 2.44 mm. The grooved portion 36 can include grooves 36a and protrusions 36b, which can be configured for ease of manufacture. As shown in Fig. 2, the grooves 36a and protrusions 36b preferably have a W-shaped profile that can be formed by rolling as opposed to machining. In this manner, the rotor 30 can be formed without an additional machining step. The grooves 36a and the protrusions 36b can also have other profiles, such as a saw tooth profile, a V-W shaped profile, and a W-W shaped profile.

[0049] The rotor 30 can be formed in a non-machined manner to reduce manufacturing complexity. For example, the rotor ring (rotor 30) can be made

by forming a suitable material into a longitudinal strip and mating the ends of the strip together (e.g., by welding). Alternatively and preferably, the rotor ring is formed as a seamless rolled ring. For example, the rotor ring is preferably formed from sheet stock low carbon steel. The sheet stock is formed into a cup shape by a cup drawing process, trimmed, and rolled to size to form the rotor ring (rotor 30). A separate rolling operation can be used to thin and shape a central portion of the ring to create the grooved portion 36. The first side 32 of the rotor ring (rotor 30) can be connected (e.g., crimped) to the outer periphery 22 of the rotor hub 20, which can be stamped from a suitable material and can optionally be formed to include the formed portion 28.

[0050] The clutch housing assembly 40 includes an annular housing 42 and a cover 52 (as shown in Figs. 1 and 4). The housing 42 and the cover 52 are preferably made of cast aluminum and are joined together to form the clutch housing assembly 40 with the cover 52 being disposed on a forward (or front) end 11a of the MRF clutch 1, and the housing 42 being disposed on an aft (or rear) end 11b of the MRF clutch 1. The forward (or front) end 11a of the MRF clutch 1 is the end of the MRF clutch 1 facing toward a forward (or front) end of a vehicle when the MRF clutch 1 is installed in the vehicle. Similarly, the aft end 11b of the MRF clutch 1 is the end of the MRF clutch 1 facing toward an aft (or rear) end of the vehicle when the MRF clutch 1 is installed in the vehicle.

[0051] The cover 52 includes an insert 150 comprising a wheel portion 54 and a ring portion 56. The insert 150 is made of a magnetically permeable ferrous material, such as a low carbon steel alloy, preferably ASTM 1010 or ASTM 1018 forged steel. The cover 52 is positioned around a portion of the insert 150. For example, the cover 52 is preferably made of aluminum and cast around the metal insert 150. As shown in Fig. 1, the housing 42 and the cover 52 connect together to enclose the rotor hub 20, the rotor 30, and a portion of the coil body 82 and to form a reservoir 16. The reservoir 16 contains a magnetorheological fluid within the clutch housing assembly 40. The clutch housing assembly 40 can also include cooling fins 142 disposed

on an external portion of the housing 42 and cooling fins 152 disposed on an external portion of the cover 52. The cooling fins 142 and 152 dissipate heat generated during operation of the MRF clutch 1.

[0052] As shown in Fig. 1, the housing 42 includes a stepped radial contact face 240, and the cover 52 includes a stepped radial contact face 250. The stepped radial contact face 240 is disposed adjacent to the stepped radial contact face 250 to form an area of contact between the housing 42 and the cover 52 that provides labyrinth sealing surfaces 50. The stepped contact faces 240 and 250 also provide pilot surfaces for radial alignment of the housing 42 and the cover 52. Additionally, the cover 52 can include a radially extending pocket 54 configured to receive a sealant, such as a polymeric sealant, or a static o-ring. The labyrinth sealing surfaces 50 and the sealant in the pocket 54 substantially prevent the leakage of MRF from the clutch housing assembly 40.

[0053] The housing 42 is rotatably disposed on the input shaft 10 so that the housing 42 is isolated from torque application from the input shaft 10. For example, a bearing set 18 can be pressed into the housing 42 (from an exterior or aft side of the housing 42) so that the bearing set 18 abuts against a surface 44 of the housing 42, as shown in Fig. 1. The bearing set 18 is any known or appropriate bearing set, preferably a 6204 size single row ball. A radial projection 48 of the housing 42 can be rolled over to lock the bearing set 18 with the housing 42. The input shaft 10 can be pressed into the bearing set 18 until a surface 10a of the input shaft 10 abuts the bearing set 18. The rotor hub 20 can be pressed onto the input shaft 10, and a radial extension 10b on an end of the input shaft 10 can be staked to lock the rotor hub 20 onto the input shaft 10. Thus, the input shaft 10 extends through the bearing set 18, the housing 42, and the rotor hub 20 and locks the bearing set 18, the housing 42, and the rotor hub 20 together.

[0054] Additionally, as shown in Fig. 1, the housing 42 can have an annular neck 46 disposed on an inner periphery of the housing 42. The annular neck 46 is sized so that a clearance between the annular neck 46 of the housing 42

and the annular neck 26 of the rotor hub 20 forms a labyrinth sealing path to substantially prevent the magnetorheological fluid in the reservoir 16 from entering the bearing set 18.

[0055] Alternatively, the housing 42 can be arranged so that the radial projection 48 and the extension forming the surface 44 are switched (i.e., relocated 180 degrees). In other words, the radial projection 48 can be located forward of the surface 44 (with respect to the vehicle) so that the bearing set 18 can be pressed into the housing 42 from an interior (or forward) side of the housing 42 to abut the surface 44. In this arrangement, the annular neck 46 of the housing is eliminated. In order to retain the labyrinth sealing function of the annular neck 46, an L-shaped washer is fitted against the bearing set 18 after the bearing set 18 is pressed into the housing 42. The radial projection 48 of the housing 42 can then be rolled over to lock the L-shaped washer and the bearing set 18 with the housing 42. The input shaft 10 can be installed as discussed above.

[0056] The cover 52 is configured to support a fan blade assembly 180, as shown in Figs. 5A and 5B. The fan blade assembly 180 includes a fan hub 182, a plurality of blades 184 extending radially from a periphery of the fan hub 182, and a ring 186 connected to an end 184a of each blade 184. The fan hub 182 is metal, preferably steel, and the blades 184 and ring 186 are plastic, preferably a nylon 6/6 material with reinforced fiberglass, that is injection molded (over-molded) around the fan hub 182. Preferably, the over-molding substantially fully encompasses the fan hub 182 (with the exception of bolt mounting pads 70) to protect the metal fan hub 182 from corrosion thus eliminating the need for additional corrosion protection.

[0057] The cover 52 is configured so that the fan hub 182 can be mounted to the cover 52. For example, the cover 52 includes a fan hub mounting portion having three angularly spaced mounting pads 70, as shown in Figs. 3 and 5. The mounting pads 70 are preferably substantially equally spaced apart from one another and are configured to enable attachment of the fan

hub 182. For example, each mounting pad 70 can include a pilot hole 72 configured to receive a fastener 190, such as a bolt.

[0058] The fan hub mounting portion can also include three angularly spaced contact pads 74, as shown in Figs. 3 and 5. The contact pads 74 are preferably substantially equally spaced apart and are configured to create a clamping load when the fan hub 182 is affixed to the hub mounting portion of the cover 52. Preferably, each mounting pad 70 has a contact pad 74 disposed on each side of the mounting pad 70 (as shown in Fig. 3). Similarly, each contact pad 74 preferably has a mounting pad 70 disposed on each side of the contact pad 74.

[0059] As best shown in Fig. 4, the contact pads 74 are offset from the mounting pads 70 in a direction aligned with the axis of rotation A-A of the input shaft 10. For example, the contact pads 74 are designed so that a plane A (which is defined by a surface 74a of at least one of the contact pads 74) is substantially parallel to and offset from a plane B (which is defined by a mounting face 70a of at least one of the mounting pads 70). The contact pads 74 are preferably offset away from the cover 52 (i.e., offset toward the aft end 11b of the MRF clutch 1) so that the contact pads 74 extend beyond the mounting pads 70.

[0060] As best shown in Fig. 5B, the fan hub 182 can include substantially flat interface pads 174a and 174b radially projecting from an inner periphery of the fan hub 182. There is one interface pad 174a for each mounting pad 70 and one interface pad 174b for each contact pad 74. The interface pads 174a and 174b are angularly spaced apart on the fan hub 182 so as to correspond to the locations of the mounting pads 70 and the interface pads 74, respectively, when the fan hub 182 is mounted to the cover 52. Each interface pad 174a includes a bolt hole to receive a fastener 190 and is configured to contact the mounting face 70a of a mounting pad when the fan hub 182 is installed on the cover 52. Similarly, each interface pad 174 is configured to contact the surface 74a of a contact pad 74 when the fan hub 182 is installed on the cover 52.

[0061] When the fan hub 182 is affixed to the mounting pads 70 and the fasteners 190 are tightened, a preload (or clamping) force develops at the contact pads 74. The preload force develops as follows. When the fan hub 182 is aligned on the hub mounting portion of the cover 52, the interface pads 174b contact the surfaces 74a (plane A) of the contact pads 74. At the same time, a gap exists between the interface pads 174a and the mounting faces 70a of the mounting pads 70 (due to the offset condition described above). When the fasteners 190 are tightened on the mounting pads 70, the gap is closed (i.e., the interface pads 174a come into contact with the mounting faces 70a). At the same time, a preload force is generated between the contact pads 74 and the interface pads 174b, which are already in contact. In this manner, the fan hub 182 is constrained in six places (i.e., at the three mounting pads 70 and at the three contact pads 74) even though only three fasteners 190 are used. Thus, during manufacture of the MRF clutch 1, the fan hub 182 can be securely affixed to the cover 52 using only three fasteners 190 while still maintaining a sufficient force to clamp the installed fan blade assembly 180 to the cover 52. Therefore, fewer components (e.g., half as many fasteners as a conventional fan clutch) and less labor are required, which results in reduced cost and weight. It will be recognized that the mounting arrangement described above can be used in applications other than fans for a clutch in a vehicle, such as any type of fan blade mounting arrangement for any type of device.

[0062] The pilot holes 72 in the mounting pads 70 can be threaded (e.g., using a thread cutter or a tap as is well known) for engagement with corresponding threaded fasteners 190. Alternatively and preferably, the pilot holes 72 can be unthreaded, and fasteners 190' (shown in Fig. 16A) can be used. The fasteners 190' are preferably tri-lobular, self-tapping fasteners, such as a tri-lobular screw. The tri-lobular shape of the fastener 190' is shown in Fig. 16. When a self-tapping fastener 190' is installed in an unthreaded pilot hole 72, the tri-lobular, self-tapping fastener rolls (forms) threads 200 in an interior surface of the pilot hole 72. As shown in Fig. 16B,

the rolled threads preserve the integrity of a shell (skin) 205 of the cast cover 52 so that porosity within the cover 52 casting is not exposed. The rolling process of the tri-lobular fastener 190' deforms the cast material forming the shell 205 without cutting the shell 205 so that a leak path from an interior (i.e., the reservoir 16) of the clutch housing assembly 40 to an exterior (i.e., into the pilot hole 72) of the clutch housing assembly 40 is not formed. Additionally, the threads 200 are formed in the pilot holes 72 at the same time the self-tapping fasteners 190' are installed the cover 52 thereby effectively combining two assembly steps (i.e., tapping and fastener installation) into one assembly step (i.e., fastener installation). Thus, the use of self-tapping fasteners 190' eliminates the need to tap (i.e., machine) threads in the cast cover 52 thereby reducing manufacturing cost and labor as well as the risk of leaks due to the porous nature of the cast aluminum material used to form the cover 52. Additionally, the self-tapping fastener 190' can be removed and reinserted such as is required when servicing the MRF clutch 1. Once removed, the self-tapping fastener 190' can even be replaced with a standard threaded fastener, such as a machine screw or bolt.

[0063] As mentioned above, the cover 52 is preferably cast around the metal insert 150, which includes the wheel portion 54 and the ring portion 56. As shown in Fig. 6C, the insert 150 can initially be formed as a single precursor piece 150' (e.g., by hot forging a suitable steel alloy blank). The aluminum cover 52 can be cast around the precursor piece 150'. The cast cover 52 and the precursor piece 150' can then be machined so that the ring portion 56 is separated from the wheel portion 54 by the slot 12, as described in U.S. Patent No. 6,585,092, incorporated by reference herein. The rotor 30 is received in the slot 12, which provides clearance for the rotor 30 so that gaps 62 and 64 exist between the rotor 30 and the wheel portion 54 and the ring portion 56, respectively. Separating the ring portion 56 and the wheel portion 54, creates a magnetic flow path that travels in the wheel portion 54 and the ring portion 56 of the insert 150. Thus, a magnetic field generated by the coil assembly 80 is prevented from shunting in the gaps 62 and 64.

According to the above-described arrangement, the rotor 30, the rotor hub 20, and the input shaft 10 function as a rotor assembly 300 of the MRF clutch 1, and the clutch housing assembly 40 functions as a stator assembly 350 of the MRF clutch 1, with the MRF enabling coupling of the rotor assembly 300 and the stator assembly 350 to thereby drive the fan blade assembly 180.

[0064] The rotor 30, the wheel portion 54, and the ring portion 56 also preferably include roughened surfaces configured to promote shear of the magnetorheological fluid near a center of the gaps 62, 64. For example, surfaces 210 of the rotor 30, the wheel portion 54, and the ring portion 56 that are in shear with the magnetorheological fluid during operation of the MRF clutch 1 preferably have a surface roughness of approximately 8 to 12 μm . The roughened surfaces 210 enable magnetic particles in the magnetorheological fluid to attach to the surfaces 210 and be tightly packed thereon. Such dense packing of the magnetic particles near the surfaces 210 enables shear of the magnetorheological fluid to occur near the center of the gaps 62, 64 rather than at or near the surfaces 210. When shear of the MRF occurs at a surface 210, a significant amount of heat is generated at the surface 210 which can lead to damage and annealing of the surface material thereby causing the material to become brittle over time and prematurely fatigue.

[0065] The insert 150 is preferably configured to reduce leakage of the magnetorheological fluid from the clutch housing assembly 40. In particular, the wheel portion 54 is preferably shaped to form a labyrinth seal path 54a (e.g., a serpentine shaped path) between the wheel portion 54 and the cover 52. The labyrinth seal path 54a is configured to direct fluid entering the labyrinth seal path 54a into the fluid reservoir 16. As shown in Fig. 1, both ends of the labyrinth seal path 54a lead to the reservoir 16. Thus, MRF in the reservoir 16 that leaks into one end of the labyrinth seal path 54a will exit at the other end of the labyrinth seal path 54a back into the reservoir 16. The labyrinth seal path 54a preferably includes a first end 54b disposed proximate the slot 12 near the second end 34 of the rotor 30 and a second end 54c

disposed near a central portion 80a of the coil assembly 80. Additionally, the wheel portion 54 can include an annular locking extension member 58 to interlock the wheel portion 54 to the cast-around cover 52 so that the wheel portion 54 and the cover 52 are anchored against separation.

[0066] The ring portion 56 of the insert 150 can include an annular extension member 57 disposed on an outer periphery of the ring portion 56, as best shown in Figs. 6, 6A, and 6B. The extension member 57 can be configured to mechanically engage an annular complimentary groove 59 disposed on an inner periphery of the cover 52 to lock the ring portion 56 and the cover 52 together. Similarly, the inner periphery of the cover 52 can include an annular extension member 57' and the outer periphery of the ring portion 56 can include a complimentary annular groove 59' to mechanically engage to lock the ring portion 56 and the cover 52 together.

[0067] Preferably, the extension members 57, 57' are annular threads 157 and the complimentary grooves 59, 59' are complementary threads 159, as best shown in Figs. 1 and 6. The annular threads 157 and the annular complimentary threads 159 are preferably square profile threads, as shown in Figs. 6 and 6B. Forming the extension members 57, 57' and the complimentary grooves 59, 59' as threads (rather than as a series of discontinuous grooves) is preferable because a thread is formed as a continuous cut, which requires fewer manufacturing steps than are required to form multiple individual grooves.

[0068] Additionally, the threads 157 and the complimentary threads 159 are preferably configured so that rotational force from the input shaft 10 causes the insert 150 and the cover 52 to more securely engage. The input shaft 10 (and therefore the clutch housing assembly 40 and fan blade assembly 180) rotates in a clockwise direction as viewed from the aft end 11b of the MRF clutch 1 and in a counterclockwise direction as viewed from the forward end 11a of the MRF clutch 1. Thus, the threads 157 and the complimentary threads 159 are preferably right hand threads. Therefore, similar to a threaded fastener, the threads 157 and the complimentary threads 159

mechanically engage the ring portion 56 of the insert 150 and the cover 52 so that movement of the ring portion 56 relative to the cover 52 causes the ring portion 56 to be more securely threaded with the cover 52. In other words, the annular threads 157 are configured to rotate in a direction of engagement with the complimentary threads 159 when the ring portion 56 moves relative to the cover 52 during operation of the MRF clutch 1.

[0069] Additionally, the locking function of the annular extension members 57, 57' and the grooves 59, 59' can be enhanced. As suggested in U.S. Patent No. 4,788,885, which is herein incorporated by reference, the housing insert 150 and the cover 52 are made of different materials (e.g., steel and aluminum, respectively, as discussed above) preferably chosen to have different coefficients of heat expansion. Thus, when the cast cover 52 is heated during operation of the MRF clutch 1, the extension members 57, 57' more positively engage the complimentary grooves 59, 59'. In this manner, the cover 52 and the ring portion 56 of the housing insert 150 are secured against separation, and leakage of the magnetorheological fluid past the locking extension members 57, 57' is reduced or prevented.

[0070] The coil assembly 80 includes a coil body 82, a coil cover 100, and a brush box (electrical connector or electrical cap) 105. As best shown in Fig. 1, a portion of the coil body 82 is enclosed between the coil cover 100 and the wheel portion 54 of the housing insert 150, and an opposite portion of the coil body 82 protrudes from the cover 52 and is enclosed by the brush box 105.

[0071] As best shown in Fig. 7, the coil body 82 includes a bobbin member 83. The bobbin member 83 is a support structure for winding a wire 95 and includes a winding ring 85 and a crossbar (or spoke) 87. The crossbar 87 is connected to a central shaft 89 and can be used, for example, to align and locate the coil body 82 in the MRF clutch 1. The central shaft 89 extends outward from a midpoint of the crossbar 87. Apertures 88 exist between the winding ring 85 and the crossbar 87.

[0072] The coil body 82 also includes a magnet 90 affixed to an end of the central shaft 89. The magnet 90 of the coil body 82 is can be segmented into

two rings 92, 94 (e.g., a positive magnetic ring and a negative magnetic ring) that are disposed on an outer periphery of the central shaft 89. The segmented magnet 90 is can be formed of a ferrite material in a PPS binder and can be segmented to provide, for example, six pulses per revolution (i.e., segmented to have six north poles and six south poles) of the coil body 82. In this manner, the segmented magnet 90 can work in conjunction with a Hall effect sensor disposed in the brush box 105 to measure fan speed thereby eliminating the need for a tone wheel in the brush box 105. Alternatively, if the magnet 90 is unsegmented, a tone wheel can be included in the brush box 105 to work in conjunction with the Hall effect sensor.

[0073] A first coil lead 192 is connected (e.g., by welding) to the first slip ring 92, and a second coil lead 194 is connected to the second slip ring 94. As best shown in Fig. 8, the first and second coil leads 192, 194 extend through the central shaft 89 into the crossbar 87. The coil body 82 further includes a coil wire 95 wrapped around the winding ring 85 to form a coil 95c. Preferably, the coil wire 95 is an epoxy coated wire, and the coil 95c has 110 turns. One end of the coil wire 95a is in mechanical and electrical contact with the first coil lead 192, and the other end of the coil wire 95b is in mechanical and electrical contact with the second coil lead 194. For example, the ends of the coil wire 95 are preferably spliced together with the respective coil lead 192, 194.

[0074] The ends 95a and 95b of the wire 95 can be configured to perform a fail safe grounding function to prevent a complete short of the coil 95c. When the MRF clutch 1 is used in a vehicle having a negative ground, the end of the wire 95 that comprises that last winding of the coil is preferably the negative lead. In this manner, the possibility of a short due to the crossover of the end of the wire is eliminated so that a complete short of the coil is prevented.

[0075] The coil body 82 is preferably over-molded with an electrically insulating, non-magnetic material 97 for encapsulating the components of the coil body 82 to prevent a shunt in the magnetic field generated by the coil body 82. The over-mold material 97 can be, for example, a polymer material.

Preferably, the over-mold material 97 is a thermosetting epoxy, in particular, the material known by the brand name Plenco (manufactured by Plastics Engineering Co.). As shown in Fig. 8, the material 97 can be applied to the winding ring 85 and the crossbar 87 to encapsulate the coil wire 95 and to form a radial projection 99. The encapsulating material 97 thus prevents the magnetic field generated by the coil body 82 from shunting between the coil cover 100 and the wheel portion 54 of the housing insert 150.

[0076] As shown in Fig. 1, the winding ring 85 of the coil body 82 sits in a circular recess (or channel) in the wheel portion 54 of the housing insert 150 and is enclosed by the coil cover 100. Thus, the winding ring 85 and a substantial portion of the crossbar 87 are located between the wheel portion 54 and the coil cover 100. Additionally, an o-ring 75 is disposed between the coil body 82 and a central portion of the cover 52 to substantially prevent MRF and/or gas vapors from leaking past. The apertures 88 in the coil body 82 enable the coil cover 100 to contact the wheel portion 54 of the housing insert 150 at a contact portion 104, as shown in Fig. 1. Thus, the coil cover 100 and the wheel portion 54 can be mechanically joined at the contact portion 104. For example, the coil cover 100 and the wheel portion 54 are preferably joined by laser welding but can also be joined by spot welding, pressing, riveting, or any other process appropriate for integrating the wheel portion 54 and the coil cover 100 for connection with the coil body 82.

[0077] When the wheel portion 54 and the coil cover 100 are joined, a peripheral portion of the wheel portion 54 contacts the radial projection 99 of the coil body 82 at an area of contact 54d, as shown in Fig. 1. Similarly, a peripheral portion of the coil cover 100 contacts the radial projection 99 of the coil body 82 at an area of contact 100d. The areas of contact 54d and 100d thus form a seal between the wheel portion 54 and the coil body 82 and between the coil cover 100 and the coil body 82 to prevent passage of the magnetorheological fluid.

[0078] The brush box 105 is a non-rotating brush assembly configured to supply power to the slip rings 92, 94. As best shown in Fig. 7A, the brush box

105 can include carbon brushes 106, brush holders 107, a brush release mechanism 107a, a circuit board assembly 108, a Hall effect sensor 109, and an ultrasonic welded cap 111. Power is supplied to the brushes 106 by the tether assembly 120. The circuit board assembly 108 can support noise suppression and signal conditioning electronics. The brushes 106, brush holders 107, and the brush release mechanism 107a are configured so that when the brush box 105 is assembled over the end of the central shaft 89, the brushes 106 are released to contact the slip rings 92, 94. As discussed above, the magnet 90 of the coil body 82 can be segmented for use in conjunction with the Hall effect sensor 109 to enable a fan speed feedback feature. Alternatively, if an unsegmented magnet is used, the brush box 105 can include a tone wheel 110.

[0079] As shown in Fig. 1, the brush box 105 is disposed (e.g., pressed) on a bearing 112 that is disposed (e.g., pressed) on a connection member 113. The connection member 113 preferably connects to the housing cover 52 via an external thread 113a, and the bearing 112 isolates the brush box 105 from rotational force imparted to the connection member 113 by the cover 52.

[0080] The tether assembly 120 is configured to deliver electrical power from an engine harness (not shown) to the brush box 105. As shown in Figs. 3 and 4, the tether assembly 120 includes an end connector 121, a molded wire port 122, and a sheath housing 123. The sheath housing 123 encloses wires 124 that transmit electrical power through the tether assembly 120 to the brush box 105. One end of the sheath housing 123 is connected (e.g., clamped) to the end connector 121. The end connector 121 is configured to interface with the engine harness, which supplies power to the tether assembly 120. The other end of the sheath housing 123 is connected (e.g., clamped) to the molded wire port 122, which is configured to interface with the brush box 105. As shown in Fig. 7A, the molded wire port 122 provides a passage into the brush box 105, thus enabling the wires 124 to contact the brushes 106 in the brush box 105 to thereby supply power to the brushes 106.

[0081] The tether assembly 120 is preferably over-molded with a suitable material, such as a rubber or elastomer, in particular a material known by the brand name of Sanaprene, for weatherproofing. The over-molding can eliminate the need for tube shielding (such as the sheath housing 123) or other insulating material to be installed separately. In this manner, the tether assembly 120 is more robust and capable of withstanding a more rugged operating environment.

[0082] In operation, when electrical power is applied to the coil body 82 through the tether 120 and the brush box 105, a magnetic field forms in the gaps 62, 64 surrounding the rotor 30. The magnetic field causes the magnetic particles suspended in the MRF to align. The aligned particles restrict motion of the MRF, which increases the energy needed to yield the MRF thereby increasing the ability of the MRF to transfer torque from the rotor assembly 300 (i.e., the input shaft 10, the rotor hub 20, and the rotor 30) to the stator assembly 350 (i.e., the clutch housing assembly 40) to thereby drive the fan blade assembly 180 attached thereto.

[0083] Thus, the rotor assembly 300 rotates at an input speed determined by, for example, the engine or the water pump pulley ratio. As power is provided to the coil body 82, the formation of the magnetic field causes the yield stress of the magnetorheological fluid to increase. Torque is transferred between the rotor assembly 300 and the stator assembly 350 when the rotor 30 rotating in the slot 12 couples with the MRF and the wheel and ring portions 54, 56 couple with the MRF and begin to rotate.

[0084] A "lockup" condition between the rotor assembly 300 and the stator assembly 350, where the rotor assembly 300 and the stator assembly 350 rotate at the same speed, is possible. However, the MRF clutch 1 typically operates at a speed differential or ratio (also known as "slip") between the rotating speed of the rotor 30 and the rotating speed of the clutch housing assembly 40 and attached fan blade assembly 180. The degree of slip is controlled by controlling the magnetic field applied to the magnetorheological fluid. Thus, by controlling the power applied to the coil body 82, the strength

of the magnetic field and the yield stress of the magnetorheological fluid is controlled. In this manner, the speed of the clutch housing assembly 40 and attached fan blade assembly 180 is virtually infinitely variable with respect to the speed of the input shaft 10.

[0085] As best shown in Figs. 9 through 13, the MRF clutch 1 preferably includes a cooling device 400 configured to direct air flow F to increase heat dissipation performance of the cooling fins 152. As best shown in Figs. 9 and 10, the cooling device 400 is installed on a front end 11a of the MRF clutch 1 and includes a diffuser element 410 and a connector element 420. The diffuser element 410 and the connector element 420 are configured to direct the air flow F toward the cooling fins 152, to increase air pressure, and to prevent stagnation of air at a central area 52a of the housing 52. As a result, the air flow F is directed into the cooling fins 152, and heat rejection within the clutch 1 is significantly improved.

[0086] The diffuser element 410 has a first surface 412 aligned to direct air toward the cooling fins 152. Preferably, the first surface 412 is a surface of a hollow, truncated cone, such as a frustum of a cone or a frustoconical section, as shown in Figs. 11 and 12. When the MRF clutch 1 is installed in a vehicle, the cooling fins 152 face toward a front end of the vehicle. As the vehicle moves, air F flows toward the cooling fins 152, as best shown in Fig. 10. The air F enters a first opening 410a of the diffuser element 410 and is directed toward a second opening 410b proximate the cooling fins 152. The first surface 412 diverges from the first opening 410a toward the second opening 410b. Thus, the diffuser element 410 is designed so that a diameter of the second opening 410b is larger than a diameter of the first opening 410a. As the air F flows through the diverging diffuser element 410, air pressure increases and the first surface 412 directs (diffuses) air toward the cooling fins 152.

[0087] The connector element 420 is disposed concentrically within the diffuser element 410 and is configured to substantially reduce stagnation of air at the central area 52a of the fan cover body 52 (e.g., at an area in the vicinity

of the cap 111 of the brush box 105). The connector element 420 preferably has a cone shaped surface to provide air flow through the diffuser element 410. As best shown in Fig. 10, the connector element 420 can be positioned over the brush box 105 so that the connector element 420 diverges in a direction toward the fan cover body 52. In other words, a small diameter end 420a of the connector element 420 is located away from the fan cover body 52, and a large diameter end 420b of the connector element 420 is located adjacent the fan cover body 52. As air flows through the diffuser element 410, the air flows along a diverging outer surface 422 of the connector element 420 rather than impinging and stagnating on the substantially flat cap 111 of the brush box 105. The connector element 420 is connected to the brush box 105, for example, by a press or interference fit or by sonic welding or staking. Alternatively, the connector element 420 can be made integral with the brush box 105.

[0088] As best shown in Fig. 11, the connector element 420 is connected to the diffuser element 410 by at least one extension member 430. Preferably, the connector element 420 includes three radially extending, angularly displaced extension members 430, as shown in Fig. 13. The extension members 430 can extend from an outer surface 422 of the connector element 420 to the first surface 412 of the diffuser element 410. Each extension member 430 can be disposed approximately 120 degrees from each other extension member 430. The diffuser element 410, the connector element 420, and the extension members 430 can be integrally formed and can be made of, for example, a polymeric material.

[0089] The diffuser element 410 and the connector element 420 also have apertures 418 and 428, respectively, as shown in Fig. 13. The apertures 418 and 428 enable the sheath housing 123 of the tether assembly 120 to pass through the diffuser element 410 and through the connector element 420 so that the tether 120 can connect to the brush box 105. Additionally, the cooling device 400 can be appropriately sized so that the cooling device 400 can be packaged in a particular vehicle between the MRF clutch 1 and a radiator.

[0090] The cooling device 400 is configured to be connected to the fan cover body 52 via the brush box 105. For example, the cooling device 400 can be integral with the brush box 105. Alternatively, the cooling device 400 can include an attachment member 440 (shown in Fig. 14). The attachment member 440 is integrally formed in the brush box 105 and is adapted to connect the cooling device 400 to the fan cover body 52. The attachment member 440 can include a central projection 442 extending from a circular base 444 of the brush box 105. The central projection 442 can engage with a corresponding aperture 428 disposed on the connection member 420. For example, the connection member 420 can be mechanically or heat laser staked onto the central projection 442 or could be connected thereto in any other known or appropriate manner.

[0091] To further enhance heat dissipation, the fan cover body 52 can include curved cooling fins 152' (as shown in Fig. 15). The curved cooling fins 152' help reduce air flow separation along the walls of the cooling fins 152' thereby reducing stagnation of air along the cooling fins 152' to provide greater heat transfer from the cooling fins 152' to the air flowing past. The cooling fins 152' are curved in a direction opposite a direction of rotation R so that air moves in an outward direction with respect to the fan cover body 52 rather than inward toward the central area 52a.

[0092] The MRF clutch 1 can also be adapted to be driven by a combined MRF coolant pump and fan clutch drive device 500. The MRF drive device 500 is configured to drive the MRF clutch 1 (fan clutch) and a coolant pump (water pump) so that a speed of the MRF clutch 1 is independent of a speed of the water pump.

[0093] The MRF drive device 500 is configured to function as an MRF clutch for the water pump. The MRF drive device 500 includes a housing 510, a coil assembly 520, a rotor assembly 530, a water pump input shaft 540, and a fan clutch input shaft 10'.

[0094] The housing 510 includes a pulley 512 configured to be driven by the engine (e.g., by a drive belt driven by a crankshaft pulley) and a housing

cover 514 connected to the pulley 512 by fasteners 505. The pulley 512 and the housing cover 514 form a reservoir 503 for containing a magnetorheological fluid. Additionally, the housing 510 includes a gasket 507 to substantially prevent leakage of the MRF out of the housing 510. The gasket 507 is preferably a polymer o-ring or an RTV-FIP gasket. The pulley 512 can be stamped from a non-ferrous material, preferably aluminum. The housing cover 514 can be extruded from a non-ferrous material, preferably aluminum. Preferably, the pulley 512 includes cooling fins 515 to improve heat rejection from the MRF drive device 500 (e.g., by creating turbulent air flow in the vicinity of the cooling fins 515).

[0095] As shown in Fig. 17, the pulley 512 is coupled to the fan clutch input shaft 10' (e.g., pressed or integrally formed) and is rotatably disposed on the water pump input shaft 540 via a bearing 516. The bearing 516 isolates the water pump input shaft 540 from the torque application by the pulley 512. The housing cover 514 is rotatably disposed on a stationary water pump housing 542 via a bearing 518. The bearings 516 and 518 allow for differential speed between the housing 510 and the water pump input shaft 540.

[0096] The coil assembly 520 is disposed within the housing 510, as shown in Fig. 17. The coil assembly 520 includes a coil body 522, a steel insert forging 524, and a steel insert ring 526. The coil body 522 is preferably press fit between the steel insert forging 524 and the steel insert ring 526. When the coil body 522 is energized by an electrical signal, the coil body 522 generates a magnetic field.

[0097] Power is supplied to the coil body 522 via brushes 528a contained in a brush holder assembly 528. The brush holder assembly 528 is connected to the housing cover 514, as shown in Fig. 17. The brushes 528a receive an electrical signal via slip rings 527a and 527b (e.g., a positive slip ring and a negative slip ring). The electrical signal is delivered to the slip rings 527a, 527b by an electrical connector 529 configured to be connected to the engine harness (not shown). The slip rings 527a, 527b and the electrical connector 529 are preferably fixed to the stationary water pump housing 542.

Additionally, the brush holder assembly 528 preferably includes a Hall effect sensor to measure differential speed between the water pump shaft 540 and the clutch housing assembly 40 of the MRF clutch 1.

[0098] The rotor assembly 530 includes a rotor 532 and a rotor hub 534. The rotor 532 is disposed so that a gap 501 (working gap) exists between the rotor 532 and the coil assembly 520, as shown in Fig. 17. The rotor hub 534 rigidly connects the rotor 532 to the water pump input shaft 540. The rotor 532 is formed of a ferrous material, preferably low carbon steel, and the rotor hub 534 is formed of a non-ferrous material, preferably aluminum.

[0099] When electrical power is applied to the coil body 522, a magnetic field forms in the gap 501. The magnetic field causes the magnetic particles suspended in the MRF to align. The aligned particles restrict motion of the MRF, which increases the energy needed to yield the MRF thereby increasing the ability of the MRF to transfer torque. Thus, the rotor assembly 530 couples with the rotating coil assembly 520 (which rotates with the housing 510). In this manner, torque is transferred from the housing 510 to the rotor assembly 530 via the MRF to thereby drive the water pump input shaft 540 and an attached water pump. In this manner, coolant is circulated.

[0100] The water pump input shaft 540 is disposed within the water pump housing 542. The water input shaft 540 is preferably made of steel, and the water pump housing 542 is preferably made of aluminum. As described above, when the coil body 522 is energized, the water pump input shaft 540 couples the pulley 512 to the water pump (not shown) to thereby circulate coolant. By controlling the power applied to the coil body 522, the strength of the magnetic field generated by the coil body 522 and the yield stress of the MRF in the gap 501 and the reservoir 503 is controlled and varied. In this manner, the speed of water pump is virtually infinitely variable with respect to the speed of the pulley 512.

[0101] Similarly, the fan clutch input shaft 10' couples the pulley 512 to the MRF clutch 1. The input shaft 10' can be coupled with the MRF clutch as described above in connection with the input shaft 10. As explained above in

connection with the operation of the MRF clutch 1, by controlling the power applied to the coil body 82, the strength of the magnetic field generated by the coil body 82 and the yield stress of the MRF in the gaps 62, 64 is controlled and varied. In this manner, the speed of the clutch housing assembly 40 and the attached fan blade assembly 180 is virtually infinitely variable with respect to the speed of the input shaft 10' (or the input shaft 10).

[0102] Thus, by controlling the respective electrical signals to the coil body 522 (water pump clutch) and to the coil body 82 (fan clutch), the water pump and the fan clutch can be driven by a common (shared) pulley 512 so that a speed of the fan clutch (and the fan blade assembly) is independent from a speed of the water pump. Moreover, the integral structure of the input shaft 10', the pulley 512, and the housing cover 514 eliminates the need for a typical headed and machined steel fan clutch shaft thereby providing weight, labor, and cost savings.

[0103] Additionally, the MRF drive device 500 preferably includes a permanent annular magnet 550 disposed on the coil body 522, for example, as shown in Fig. 18. The permanent magnet 550 is preferably low carbon steel. The permanent magnet 550 is configured to perform a fail safe function by enabling the MRF drive device 500 to fail ON in the event power to the coil body 22 is cut off (e.g., due to an open circuit or catastrophic failure). The permanent magnet 550 generates a permanent magnetic field in the gap 501 and in the MRF surrounding the rotor 530. The permanent magnetic field is sufficient to provide a base threshold of MRF torque transfer. Thus, the water pump can be driven even if the coil body 522 is de-energized. In this manner, the engine is protected from overheating because coolant continues to flow even if power to the MRF drive device 500 is discontinued.

[0104] An MRF clutch according to the present invention can include all of the above-described the features, if desired. Alternatively, an MRF clutch according to the present invention can include any one of or any subset of the above-described features. Thus, embodiments according to the present invention contemplate all possible permutations and combinations of the

above-described features. For example, an MRF clutch could include a subset of features including the grooved portion 36 on the rotor 30, the formed portion 28 on the rotor hub 20, and the roughened surfaces 210. Another subset of features could include the mounting pads 70, the contact pads 74, and the self-tapping fasteners 190'. Another subset of features could include the locking extension members 57 and 57', the complementary grooves 59 and 59', and the labyrinth seal path 54a formed between the housing insert 150 and the cover 52. Yet another subset of features could include the cooling element 400 and the curved fins 152'. Additional subsets include each of the above-described subsets with the MRF clutch being coupled to a water pump via the MRF drive device 500.

[0105] Thus, according to the embodiments described above, a more robust, manufacturable, and operable MRF clutch for a fan drive assembly is provided.

[0106] Modifications and other embodiments of the invention will be apparent to those skilled in the art from consideration of the specification and practice of the invention disclosed herein. It is intended that the specification and examples be considered as exemplary only, the scope of the invention being limited only by the appended claims.

WHAT IS CLAIMED IS:

1. A fan mounting arrangement for a fan clutch of the type in which a fan blade hub is fastened to a hub mounting portion of a fan housing having an axis of rotation, the fan mounting arrangement comprising:

three angularly spaced mounting pad portions located on the hub mounting portion and each mounting pad portion configured to have the fan blade hub fastened thereto; and

three contact pad portions angularly disposed on the hub mounting portion such that each contact pad portion has a mounting pad portion on each side of it and each mounting pad portion has a contact pad portion on each side of it,

wherein the contact pad portions are offset from the mounting pad portions in a direction aligned with an axis of rotation of the fan clutch so that the contact pad portions apply a force to the fan blade hub when the fan blade hub is securely fastened to the hub mounting portion such that fewer fasteners are needed to securely fasten the fan blade to the fan clutch.

2. The fan mounting arrangement of claim 1, wherein the mounting pads each include a bolt hole for mounting the fan blade hub to the mounting portion of the housing.

3. A mounting arrangement for mounting a fan blade having a fan blade hub to a housing, the mounting arrangement comprising:

the housing including a mounting portion for having the fan blade hub mounted thereto,

wherein the mounting portion of the housing includes a plurality of angularly spaced mounting pads and a plurality of angularly spaced contact pads, and

wherein the contact pads are configured to apply a force in a direction aligned with an axis of rotation of the housing to the fan blade hub when the fan blade hub is mounted to the mounting portion of the housing.

4. The fan mounting arrangement of claim 3, wherein at least one contact pad is offset from at least one mounting pad.

5. The fan mounting arrangement of claim 4, wherein the contact pad is offset from the housing in a direction aligned with the axis of rotation of the housing.

6. The fan mounting arrangement of claim 3, wherein there are three mounting pads and three contact pads.

7. A fan clutch assembly including the fan mounting arrangement of claim 3.

8. A magnetorheological fluid clutch, comprising:
an input shaft;
a cast housing including a first housing portion engaged with a coil assembly and a second housing portion rotatably disposed on the input shaft;
and

a rotor assembly disposed between the first housing portion and the second housing portion,

wherein the first housing portion includes a hub mounting portion for mounting a fan blade hub,

wherein the hub mounting portion includes three angularly disposed mounting pad portions each configured to receive a fastener for mounting the fan blade hub thereto and three angularly disposed contact pad portions, and

wherein the contact pad portions are offset, in a direction aligned with the axis of rotation of the input shaft, from the mounting pad portions so that

the contact pad portions apply a force to the fan blade hub when the fan blade hub is securely fastened to the hub mounting portion.

9. An improved fan mounting arrangement for a fan clutch, wherein the fan clutch includes a housing having a hub mounting portion and a fan blade hub mounted thereto, the fan mounting arrangement comprising:

fasteners having tri-lobular threads,

wherein the tri-lobular threads are engaged with corresponding roll formed threads in the fan housing, the roll formed threads being configured to substantially reduce leakage of fluid from an interior of the fan housing to an exterior of the fan housing.

10. A fan mounting arrangement, comprising:

a fan housing including a hub mounting portion for mounting a fan blade hub;

a fan blade having a plurality of blades extending from a periphery of a hub; and

fasteners connecting the fan blade hub to the hub mounting portion of the fan housing,

wherein the fasteners include tri-lobular threads engaged with corresponding threads of the fan housing, and

wherein the corresponding threads are roll formed threads to substantially reduce leakage of fluid past the corresponding threads from an interior of the fan housing to an exterior of the fan housing.

11. A fan clutch including the fan mounting arrangement of claim 10.

12. The fan clutch of claim 11, wherein the fan clutch comprises a magnetorheological fluid fan clutch.

13. A method of mounting a fan blade to a fan housing, comprising:
 - providing a cast fan housing including a hub mounting portion, wherein the hub mounting portion includes unthreaded pilot holes for mounting a fan blade hub to the hub mounting portion;
 - providing a fan blade having a plurality of blades extending from a periphery of a hub, wherein the hub includes bolt holes arranged to correspond to the pilot holes on the hub mounting portion;
 - providing at least one fastener having tri-lobular threads;
 - aligning the bolt holes of the fan blade hub with the corresponding pilot holes of the hub mounting portion;
 - inserting the fastener into one of the bolt holes until the fastener contacts a wall of the pilot hole;
 - forming rolled threads in the wall of the pilot hole by rotating the fastener.
14. The method of claim 13, further comprising applying a torque of approximately 30 N-m to the fastener.
15. An viscous fluid clutch comprising:
 - a housing including a first housing portion cast around an annular housing insert and a second housing portion connected to the first housing portion and defining a fluid reservoir contained by the first and second housing portions; and
 - a labyrinth seal path formed between the housing insert and the first housing portion and having a first end and a second end such that any fluid entering the labyrinth seal path is returned to the fluid reservoir between the first and second housing portions.
16. A viscous fluid clutch, comprising:
 - an input shaft;
 - a rotor assembly connected to the input shaft;

an annular housing insert;
a coil assembly operatively connected to the housing insert;
a housing including a first housing portion cast around the housing insert and a second housing portion connected for rotation with the first housing portion and rotatably disposed on the input shaft; and
a fluid reservoir disposed between the first housing portion and the second housing portion,
wherein the first housing portion and the housing insert form there between a labyrinth seal having a first end and a second end wherein each of the first end and the second end of the labyrinth path communicate with the fluid reservoir such that any fluid entering the labyrinth seal is returned to the fluid reservoir.

17. The viscous fluid clutch of claim 16, wherein the first end of the labyrinth seal is located toward an outer radial end of the rotor and the second end is located toward a central portion of the coil assembly.

18. The viscous fluid clutch of claim 16, wherein the housing insert includes an annular locking extension portion for interlocking the housing insert and the first housing portion.

19. The viscous fluid clutch of claim 16, wherein the viscous fluid comprises a magnetorheological fluid.

20. A fan drive assembly for use in a vehicle including the viscous fluid clutch of claim 16.

21. A fluid clutch of the type in which a first housing portion includes a cast housing portion cast around an annular housing insert and a second housing to be connected to the first housing portion, the connected first and second

housing portions adapted to be rotatably disposed on an input shaft, the fluid clutch comprising:

an annular extension member located on one of a periphery of the first housing insert and the cast housing portion and an annular complimentary groove located on the other of the periphery of the first housing insert and the cast housing portion, wherein the extension member mechanically engages the complimentary groove to lock the housing insert and the cast housing portion; and

wherein the cast housing portion has a first associated coefficient of heat expansion and the housing insert has a second associated coefficient of heat expansion different than the first coefficient of heat expansion such that when the first housing portion is heated when the clutch fan is in use, the extension member more positively engages the complimentary groove and prevents fluid from leaking there past.

22. The improved housing of claim 21, wherein the annular extension member comprises an annular thread and the complimentary groove comprises an annular complimentary thread mechanically engaging the housing insert to the cast housing portion such that movement of the insert relative to the cast housing portion causes the insert to be more securely threaded with the cast housing portion.

23. The improved housing of claim 21, wherein the cast housing portion comprises a radially extending annular surface.

24. A fluid clutch, comprising:
an input shaft;
a rotor connected to the input shaft;
a housing including a first housing portion connected to a second housing portion, wherein the second housing portion is rotatably disposed on the input shaft;

an annular housing insert, wherein the first housing portion is cast around the housing insert; and
a coil assembly engaged with the housing insert,
wherein one of a periphery of the first housing portion and the housing insert includes an annular projection and a periphery of the other of the first housing portion and the housing insert includes an annular groove, and
wherein the annular projection and the annular groove mechanically engage to prevent separation of the first housing portion and the annular groove.

25. The fluid clutch of claim 24, wherein the first housing portion comprises a radially extending surface.

26. The fluid clutch of claim 24, wherein the first housing portion comprises a material having a first coefficient of heat expansion and the housing insert comprises a material having a second coefficient of heat expansion different than the first coefficient of heat expansion.

27. The fluid clutch of claim 24, wherein the annular projection comprises an annular thread and the annular groove comprises an annular complimentary thread.

28. The fluid clutch of claim 27, wherein the annular thread is a square profile thread.

29. The fluid clutch of claim 27, wherein the annular thread and the complimentary thread mechanically engage the first housing portion and the housing insert so that movement of the housing insert relative to the first housing portion is in a direction of engagement of the annular thread and the complimentary thread.

30. The fluid clutch of claim 29, wherein the annular thread is a right hand thread and the fluid clutch is designed to rotate in a counterclockwise direction as viewed from a forward end of the fluid clutch.

31. The fluid clutch of claim 24, wherein the fluid comprises a viscous fluid.

32. The fluid clutch of claim 31, wherein the viscous fluid comprises a magnetorheological fluid.

33. A fan drive assembly for use in a vehicle, the fan drive assembly including the fluid clutch of claim 24.

34. A fluid clutch for use in a vehicle, the fluid clutch including a rotor having a rotor hub driven by an input shaft and a rotor surface having an end connected to an outer periphery of the rotor hub, the fluid clutch comprising:
the rotor surface including a first portion, a second portion, and a roll formed portion disposed between the first and second portions,
wherein the first and second portions of the rotor each have a thickness sufficiently greater than a thickness of the roll formed portion such that a magnetic flux path in the fluid clutch will have a substantial portion of a magnetic field flow around the roll formed portion as compared to a portion of the magnetic field flow that flows through the roll formed portion.

35. The fluid clutch of claim 34, wherein the roll formed portion of the rotor has a saw tooth profile.

36. The fluid clutch of claim 34 wherein the roll formed portion of the rotor has a V-W shaped profile.

37. The fluid clutch of claim 34 wherein the roll formed portion of the rotor has a W-W shaped profile.

38. A magnetorheological fluid clutch, comprising:
an input shaft;
a coil assembly for generating a magnetic field;
a housing comprising a stator; and
a rotor disposed in the housing,
wherein the rotor includes a radially extending hub driven by the input shaft and an annular rotor ring connected to the hub, and
wherein the rotor ring includes a first portion, a second portion, and a thinned center portion disposed between the first and second portions to prevent a shunt in the magnetic field, and
wherein the thinned portion has a saw tooth shaped profile.
39. The magnetorheological fluid clutch of claim 38, wherein the thickness of the first portion and the thickness of the second portion are at least seven times greater than the thickness of the rolled portion.
40. The magnetorheological fluid clutch of claim 38, wherein the roll formed portion is formed to include grooves and protrusions.
41. The magnetorheological fluid clutch of claim 40, wherein the grooves and protrusions form a W-shape.
42. The magnetorheological fluid clutch of claim 38, wherein the roll formed portion is formed without cutting.
43. The magnetorheological fluid clutch of claim 38, wherein the rotor ring comprises a ferrous metal.
44. A fan drive assembly for use in a vehicle, the fan drive assembly including the magnetorheological fluid clutch of claim 38.

45. An improved rotor assembly for use in a magnetorheological fluid clutch for use in a vehicle, the rotor assembly including a hub driven by an input shaft and a rotor ring having a first side and a second opposite side, the first side connected to an outer periphery of the hub, wherein the rotor assembly is disposed between a first housing portion and a second housing portion, the improvement comprising:

an annularly extending curved portion formed in the hub and configured to compensate for dimensional changes of the hub due to temperature variation during operation of the clutch,

wherein the curved portion includes a concave surface disposed on a side of the hub facing in a direction toward the second side of the rotor ring.

46. A viscous fluid clutch, comprising:

an input shaft;

a coil assembly;

a cast housing including a first housing portion connected to the coil assembly and a second housing portion rotatably disposed on the input shaft; and

a rotor assembly disposed between the first housing portion and the second housing portion,

wherein the rotor assembly includes a hub disposed on the input shaft and a rotor formed as a ring and having a side connected to an outer periphery of the hub, and

wherein the hub includes an annularly extending curved portion configured to compensate for dimensional changes of the hub and the effect on the rotor due to temperature variation of the viscous fluid clutch during operation.

47. The viscous fluid clutch of claim 46, wherein the rotor extends away from the hub and the curved portion of the hub includes a concave surface facing toward a direction of extension of the rotor ring.

48. The viscous fluid clutch of claim 47, wherein the curved portion is located to have the concave surface offset from the outer periphery of the hub.

49. The viscous fluid clutch of claim 48, wherein the concave surface is offset in a direction opposite from the direction of extension of the rotor ring.

50. The viscous fluid clutch of claim 50, wherein the rotor ring extends away from the hub and the curved portion of the hub includes a convex surface facing toward a direction opposite from a direction of extension of the rotor ring.

51. The viscous fluid clutch of claim 50, wherein the curved portion is located so that the convex surface is offset from the outer periphery of the hub.

52. The viscous fluid clutch of claim 51, wherein the concave surface is offset in the direction opposite from the direction of extension of the rotor ring.

53. The viscous fluid clutch of claim 46, wherein the curved portion comprises a concave surface facing toward the first housing portion and a convex surface facing toward the second housing portion.

54. The viscous fluid clutch of claim 46, wherein the rotor ring extends in a direction away from the hub and the curved portion of the hub comprises a concave surface disposed on the side of the hub facing in the direction of extension of the rotor ring.

55. The viscous fluid clutch of claim 46, wherein the viscous fluid clutch comprises a magnetorheological fluid clutch.

56. A fan drive assembly including the viscous fluid clutch of claim 46.

57. A method of making a rotor assembly for use in a viscous fluid clutch, the method comprising the steps of:

providing a magnetic material;

forming the magnetic material into a rotor ring;

roll forming the rotor ring to include a thinned central portion, wherein the first and second portions each have a thickness greater than a thickness of the thinned central portion;

providing a hub member; and

connecting the rotor ring to the hub member.

58. The method of claim 57, wherein the step of forming the magnetic material into a rotor ring includes the steps of providing a sheet of the magnetic material, cup drawing the magnetic material into a cup-shaped member, trimming the cup-shaped member to form a ring, and roll forming the ring.

59. The method of claim 58, further comprising the step of stamping the hub member and forming a curved portion between an inner periphery of the hub member and an outer periphery of the hub member.

60. The method of claim 57, wherein the step of connecting the rotor ring to the hub member includes crimping one of the first portion and the second portion of the rotor ring to an outer periphery of the hub member.

61. A coil assembly for a viscous fluid clutch, comprising:
a bobbin including a winding ring having a crossbar;
a central shaft extending from the crossbar;
a first magnet disposed on an outer periphery of the central shaft;
a second magnet disposed on an outer periphery of the central shaft;
a first lead connected to the first magnet and extending through the central shaft into a first portion of the cross bar;
a second lead connected to the second magnet and extending through the central shaft into a second portion of the cross bar; and
a wire wrapped around the winding ring and including a first end in contact with the first lead in the first portion of the cross bar and a second end in contact with the second lead in the second portion of the crossbar,
wherein the bobbin, the winding ring, the central shaft, and the wire are over-molded with a resin.
62. The coil assembly of claim 61, wherein the resin comprises a polymer material.
63. The coil assembly of claim 61, wherein the resin comprises a thermosetting epoxy.
64. A magnetorheological fluid clutch including the coil assembly of claim 61.
65. The magnetorheological fluid clutch of claim 64, wherein the winding ring and the crossbar are disposed between a first housing cover and a coil cover.
66. The magnetorheological fluid clutch of claim 65, wherein the first housing cover and the coil cover are mechanically joined.

67. A fan drive assembly for use in a vehicle including the magnetorheological fluid clutch of claim 64.

68. An improved cooling device for a vehicle fan clutch having a housing including cooling fins disposed on the housing facing toward a direction of air flow, the cooling device comprising:

- a diffuser element including a first surface aligned to direct air toward the cooling fins; and

- a connector element having a first portion connected to the diffuser element and a second portion for connection with the vehicle fan clutch,

- wherein the diffuser element and the connector element are configured to prevent stagnation of the air at a central area of the housing.

69. An air-directing device to increase the cooling effect for a housing having a plurality of fins located on an external surface of the housing, the air-directing device comprising:

- a diffuser element configured to be disposed on a front end of the finned housing;

- a connector element disposed within the diffuser element,

- wherein the diffuser element and the connector element are configured to reduce stagnation of air in the vicinity of the finned housing when air is flowing toward the front end of the finned housing.

70. The air directing device of claim 69, wherein the diffuser element comprises a frustoconical diffuser element.

71. The air-directing device of claim 69, wherein the connector element includes a cone shaped portion having a larger diameter end located adjacent the housing and a smaller diameter end located away from the housing.

72. The air-directing device of claim 69, wherein the diffuser element is connected to the connector element by at least one extension member.

73. The air-directing device of claim 72, wherein the connector element is connected to the diffuser element by three radially extending, angularly displaced extension members.

74. A fan clutch including the air-directing device of claim 69.

75. The fan clutch of claim 74, wherein the connector element is connected to an electrical cap disposed on a fan clutch housing.

76. The fan clutch of claim 75, wherein the fan clutch housing includes curved fins configured to reduce flow separation along the fins.

77. The fan clutch of claim 74, wherein the fan clutch comprises a magnetorheological fluid fan clutch.

78. A combined coolant pump and fan assembly for a vehicle of the type in which an engine driven pulley is connected to the coolant pump and to the fan, the assembly comprising:

a first viscous fluid clutch coupled to the pulley; and

a second viscous fluid clutch coupled to the pulley,

wherein the first viscous fluid clutch is configured to drive the fan and the second viscous fluid clutch is configured to drive the coolant pump, and

wherein the first and second viscous fluid clutches are configured so that a speed of the first clutch is independently variable from a speed of the second clutch.

79. A combined fan clutch and coolant pump assembly for a vehicle, comprising:
- a pulley configured to be driven by an engine;
 - a viscous fluid fan clutch coupled to the pulley; and
 - a viscous fluid coolant pump clutch coupled to the pulley,
- wherein the viscous fluid fan clutch and the viscous fluid coolant pump clutch are configured so that a speed of the fan clutch is independent of a speed of the coolant pump.
80. The combined fan clutch and coolant pump assembly of claim 79, wherein the viscous fluid fan clutch includes an input shaft coupled to the pulley, a rotor assembly connected to the input shaft; a coil assembly; a first housing cover connected to the coil assembly; and a second housing cover rotatably disposed on the input shaft.
81. The combined fan clutch and coolant pump assembly of claim 79, wherein the viscous fluid coolant pump clutch includes a coil assembly disposed within the pulley; a rotor assembly; a coolant pump input shaft coupled to the rotor assembly; and a housing cover connected to the pulley.
82. The combined fan clutch and coolant pump assembly of claim 81, wherein the viscous fluid coolant pump clutch includes a permanent magnet configured to enable the rotor to drive the coolant pump input shaft when the coil assembly is de-energized.
83. The combined fan clutch and coolant pump assembly of claim 79, wherein the viscous fluid comprises a magnetorheological fluid.

[illegible]

Fig. 2




Fig. 2A




Fig. 2B





Fig. 3






Fig. 5




Fig. 5A

Fig. 5B




Fig. 6




Fig. 6A




Fig. 6B




Fig. 6C




Fig. 7




Fig. 7A





Fig. 8






Fig. 9




Fig. 10





Fig. 11

Fig. 12






Fig. 13




Fig. 14




Fig. 15

Fig. 16




Fig. 16A




Fig. 16B





Fig. 18



Application Data Sheet

Application Information

| | |
|---|-----------------|
| Application Type:: | Provisional |
| Subject Matter:: | Utility |
| Suggested classification:: | |
| Suggested Group Art Unit:: | |
| CD-ROM or CD-R?:: | None |
| Computer Readable Form (CRF)?:: | No |
| Title:: | CLUTCH ASSEMBLY |
| Attorney Docket Number:: | 032968-0105 |
| Request for Early Publication?:: | No |
| Request for Non-Publication?:: | No |
| Suggested Drawing Figure:: | |
| Total Drawing Sheets:: | 21 |
| Small Entity?:: | No |
| Petition included?:: | No |
| Secrecy Order in Parent Appl.?:: | No |

Applicant Information

| | |
|--------------------------------------|-------------------|
| Applicant Authority Type:: | Inventor |
| Primary Citizenship Country:: | US |
| Status:: | Full Capacity |
| Given Name:: | Lawrence Craig |
| Family Name:: | KENNEDY |
| City of Residence:: | Commerce Township |

State or Province of Residence:: MI
Country of Residence:: US
Street of mailing address:: 4865 Ledgewood Drive
City of mailing address:: Commerce Township
State or Province of mailing address:: MI
Postal or Zip Code of mailing address:: 48382

Applicant Authority Type:: Inventor
Primary Citizenship Country:: US
Status:: Full Capacity
Given Name:: James F.
Family Name:: GALLAGHER
City of Residence:: Howell
State or Province of Residence:: MI
Country of Residence:: US
Street of mailing address:: 1151 North Alstott Drive
City of mailing address:: Howell
State or Province of mailing address:: MI
Postal or Zip Code of mailing address:: 48843

Applicant Authority Type:: Inventor
Primary Citizenship Country:: US
Status:: Full Capacity
Given Name:: Philip
Family Name:: STEPHENSON

City of Residence:: Dexter
State or Province of Residence:: MI
Country of Residence:: US
Street of mailing address:: 2740 Bent Tree Drive
City of mailing address:: Dexter
State or Province of mailing address:: MI
Postal or Zip Code of mailing address:: 48130

Applicant Authority Type:: Inventor
Primary Citizenship Country:: US
Status:: Full Capacity
Given Name:: Gregory
Family Name:: MACK
City of Residence:: Dansville
State or Province of Residence:: MI
Country of Residence:: US
Street of mailing address:: 1476 Adams Street
P.O. Box 49
City of mailing address:: Dansville
State or Province of mailing address:: MI
Postal or Zip Code of mailing address:: 48819

Correspondence Information

Correspondence Customer Number:: 22428

E-Mail address:: PTOMailWashington@Foley.com

Representative Information

| | | |
|---|-------|--|
| Representative Customer Number:: | 22428 | |
|---|-------|--|

Domestic Priority Information

| | | | |
|----------------------|--------------------------|-----------------------------|-----------------------------|
| Application:: | Continuity Type:: | Parent Application:: | Parent Filing Date:: |
| | | | |

Foreign Priority Information

| | | | |
|------------------|-----------------------------|----------------------|---------------------------|
| Country:: | Application number:: | Filing Date:: | Priority Claimed:: |
| | | | |

Assignee Information

Assignee name::